



NOTCH

Manufacturing, Inc.



6 BALE TRANSPORTS

Designed for 2,000 lbs. bales – 4.5' to 6' diameter

All fabricated components are made with alloy steel

Unique box frame design for maximum strength

Cradles are not connected to each other, only to the main beam; this allows loading both sides from either side



4 WHEEL 6 BALE TRANSPORT - BT6-4

Bale capacity: 18,000 lbs.

Main beam: 10" x 4" x 5/16" tubing

Removable 2" spindle, grease fittings on all hubs, 15"x 8"x 6 bolt wheels

Tricycle type steering for 90° turning and quick hitch tongue for quick easy hook up

Shown with standard fenders



2 WHEEL 6 BALE TRANSPORT - BT6-2

Bale capacity: 12,000 lbs.

Main beam: 10" x 4" x 5/16" tubing

Removable 2 1/4" rear spindle, 22.5"x 8.25"x 8 bolt wheels, grease fittings on all hubs

T-post for field loading, storable 5 ton jack

Shown with standard fenders



OPTIONAL LIGHT PACKAGE

Tail lights: running, stop and turn lights
All enclosed in flush mount for protection



OPTIONAL BRAKE & LIGHT PACKAGE

Light package plus electric rear brakes
16" dual wheels



OPTIONAL TWO BALE CRADLE

Two bale bolt on cradle in place of fenders
Available on all transports

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com